



**Xilin**  
**CQDH15A**

China

**onQ-30921**

WAREHOUSE MOVERS & LIFTS - REACH TRUCKS & STACKERS  
NEW - SALE

|                                          |                                                |
|------------------------------------------|------------------------------------------------|
| <b>Date Listed</b>                       | 28 Apr 2023                                    |
| <b>Reference</b>                         | CQDH15A                                        |
| <b>Power Type</b>                        | Battery Electric                               |
| <b>Lift Capacity</b>                     | 1,500 kg(3,307 lb)                             |
| <b>Mast Type</b>                         | Triples (3 Stage)                              |
| <b>Maximum Lift Height</b>               | 5,600 mm(220 in)                               |
| <b>Tyre Type</b>                         | Polyurethane / Vulkollan                       |
| <b>Machine Height<br/>(Mast Lowered)</b> | 2,505 mm(99 in)                                |
| <b>Machine Features</b>                  | Mast full free lift<br>Pantograph/double reach |

**ADDITIONAL INFORMATION**

**STRUCTURAL** • Reach stacker with very compact design, have different option with platform or without platform. • Low gravity, ensure safety operation. • Water proof and dust proof motor structure, keeps the braking and motor more durable and reliable. • Multi function display with BDI, hour meter and fault code. • Vertical driving wheel ensures convenient maintenance and small turning radius. • The mast and frame are dividable and exchangeable.

**SAFETY AND EFFICIENCY** • Advanced AC drive motor eliminates replacement of carbon brush, with good ramp starting performance. • Use Germany Frei handle to control driving speed, lifting/lowering speed, sideshift, fork reach and tilting. • Cylinder have safety explosion proof valve, to avoid fork dropping suddenly when oil tube is broken. ensure the safety of operator. • Automatic speed deceleration when lifting height is up 1.8M. • Mast with micro switch limit the cylinder lifting height, avoid mast shock problems. • Low voltage protection setting prolongs the battery life. (while battery less 20% only can drive no lifting) • Option EPS power steering system, makes steering more light an reliable.

**SERVICE ABILITY** • Platform and protection arm are disassembled, easy maintenance. • The electronic components concentrated simplifies the circuit and makes easily assemble and access. • Battery equipped with protect device, the trucks will automatic cut off power will when battery is under charging.